



PLCV5 series of projector ceiling lifts — PLCV5.1 & PLCV5.2

The smaller models of PLCV5 series, provide a reliable solution for every day needs in offices and homes. Easy to install and accurate in motion require little room inside the false ceiling and offer flexibility in application setup and design with optional drop down ability (increase in number of scissor sets), available at ordering stage.



Model	PLCV5.1	PLCV5.1 +XD	PLCV5.1 +2 x XD	PLCV5.2	PLCV5.2 +XD	PLCV5.2 +2 x XD
Space inside carriage for projector (WxL)	525mm x 440mm			420mm x 440mm		
Maximum load capacity (projector+ceiling cover)	20kg					
Minimum required inner ceiling depth (height)	72mm for projectors with L <345mm or 105mm for projectors with L >345mm +projector height	112mm +projector height	157mm +projector height	72mm for projectors with L <345mm or 105mm for projectors with L >345mm +projector height	112mm +projector height	157mm +projector height
Vertical motion length	200mm	400mm	600mm	200mm	400mm	600mm
Standard color	powder coating in RAL 9005 black					
Power supply	230VAC					
Standard control method	wall switch over 230VAC					
Optional controls	RF remote control, dry contacts control box, RS 232/485 control board ports (each one alternative to the other)					

ALL RIGHTS ARE STRICTLY RESERVED.

REPRODUCTION OR ISSUE TO 3RD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORIZATION BY UNITECH SYSTEMS

All above information may change by the manufacturer without prior notice or obligation of any kind.