



## PLCV5 series of projector ceiling lifts — PLCV5.3

The larger models of PLCV5 series, provide flexible and reliable solutions for almost every projector application.

Facilitating the installation with features like pre-drilled projector plate, cable chain for safe cable management, optional drop down ability (increase in number of scissor sets) available at ordering stage and accurate motion, PLCV5.3 & PLCV5.3HD cover the needs of all regular projectors.



Model	PLCV5.3	PLCV5.3 +XD300	PLCV5.3 +2 x XD300	PLCV5.3HD	PLCV5.3HD +XD300	PLCV5.3HD +2 x XD300
Space inside carriage for projector (WxL)	555mm x 495mm					
Maximum load capacity (projector+ceiling cover)	20kg			35kg	30kg	
Minimum required inner ceiling depth (height) above false ceiling	<b>71mm</b>	<b>106mm</b>	<b>141mm</b>	<b>71mm</b>	<b>106mm</b>	<b>141mm</b>
	+projector height	+projector height	+projector height	+projector height	+projector height	+projector height
Vertical motion length	300mm	600mm	900mm	300mm	600mm	900mm
Lift dimensions (WxD)	690mm x 596mm					
Standard color	powder coating in RAL 9005 black					
Power supply	230VAC					
Standard control method	wall switch over 230VAC					
Optional controls	RF remote control, dry contacts control box, RS 232/485 ports on external control box (each one alternative to the other)					

ALL RIGHTS ARE STRICTLY RESERVED.

REPRODUCTION OR ISSUE TO 3RD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORIZATION BY UNITECH SYSTEMS

All above information may change by the manufacturer without prior notice or obligation of any kind.