

## PLCV5 series of projector ceiling lifts — PLCV5.4

The larger models of PLCV5 series, provide flexible and reliable solutions for almost every projector application.

Facilitating the installation with features like pre-drilled projector plate, cable chain for safe cable management, optional drop down ability (increase in number of scissor sets) available only during ordering time and accurate motion, PLCV5.4 & PLCV5.4HD series cover the needs of all professional projectors.



| Model                                                             | PLCV5.4                                                                                                                   | PLCV5.4<br>+XD500                 | PLCV5.4<br>+2 x XD500             | PLCV5.4HD                        | PLCV5.4HD<br>+XD500               | PLCV5.4HD<br>+2 x XD500           |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----------------------------------|----------------------------------|-----------------------------------|-----------------------------------|
| Space inside carriage for projector (WxL)                         | 600mm x 745mm                                                                                                             |                                   |                                   |                                  |                                   |                                   |
| Maximum load capacity (projector+ceiling cover)                   | 35kg                                                                                                                      |                                   |                                   | 50kg                             | 45kg                              |                                   |
| Minimum required inner ceiling depth (height) above false ceiling | <b>75mm</b><br>+projector height                                                                                          | <b>125mm</b><br>+projector height | <b>175mm</b><br>+projector height | <b>75mm</b><br>+projector height | <b>125mm</b><br>+projector height | <b>175mm</b><br>+projector height |
| Vertical motion length                                            | 500mm                                                                                                                     | 1000mm                            | 1500mm                            | 500mm                            | 1000mm                            | 1500mm                            |
| Lift dimensions (WxD)                                             | 720mm x 850mm                                                                                                             |                                   |                                   |                                  |                                   |                                   |
| Standard color                                                    | powder coating in RAL 9005 black                                                                                          |                                   |                                   |                                  |                                   |                                   |
| Power supply                                                      | 230VAC                                                                                                                    |                                   |                                   |                                  |                                   |                                   |
| Standard control method                                           | wall switch over 230VAC                                                                                                   |                                   |                                   |                                  |                                   |                                   |
| Optional controls                                                 | RF remote control, dry contacts control box, RS 232/485 ports on external control box (each one alternative to the other) |                                   |                                   |                                  |                                   |                                   |